74

AUBURN CLUTCH PARTS

USAGE: Original equipment on all tractors except serial Nos. 9488 thru 21135 on which the ROCKFORD clutch (See page 73) was a possible alternate as a factory option.

	RETAINER, shifting sleeve bearing CAPSCREW, 3/8" x 5/8" LOCKWASHER, 3/8"	4 4 1	042142 035979 904206	3 3 4 3
	SHIELD, grease CAPSCREW, 5/16"NF x 3/4" Also attach brake disc LOCKWASHER, 5/16"	661	050575 057927 904205	31
	FACING KIT, brake disc (Includes RIVETS indented below) RIVET, tubular, brass, flat-hd., 3/16" x 7/16"	10	081756 911131	30
	DISC ASSEMBLY, clutch brake, front (Includes item 30)	I	050578	29
	Includes item	,—	078134	28
082877	RACE, shifting yoke needle bearing	2	056864	27
	RING, locking, shifting sleeve bearing	1	042144	26
	BEARING, ball, shifting sleeve	1	042994	25
		1	042141	24
	CAPSCREW, spring retainer (dog-pt., 5/16"NC x 1-1/16")	ω	074614	23
	RETAINER, pressure plate retracting spring	ω	042129	22
/	SPRING, pressure plate retracting	w	042130	21
	SCREW (hex-hd., 3/8"NF x 1", drilled end) LOCKWASHER, internal teeth, 3/8" PIN, cotter, 3/32" x 3/4"		055760 906960 900801	20
a 18)	BUSHING, shifting sleeve (bronze) (Furnished only as part of item 18)	2	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	19
	below) cating, straight, 1/8"NPT	-	914465	
	SLEEVE ASSEMBLY, shifting (Includes items 17 and 19; also	1	078116	18
	BUSHING, shifting sleeve (steel)	6	048195	17
	PIN, actuating lever link (5/16" diam., 1" long) PIN, cotter, 3/32" x 1/2"	12 12	048173 904001	16
	LINK, actuating lever	6	055759	15
	NUT, castle, 5/16''NF PIN, cotter, 3/32" x 1/2"	22	913238 904001	
	CAPSCREW, retaining, adjusting ring (fil-hd., 5/16"NF x 1",	2	055756	14
	PLATE, back	1	055753	13
î	RING ASSEMBLY, adjusting (Includes 6 wear PLATES, 6 BRACK ETS, 6 CLIPS, 24 RIVETS. Serviced only as a unit)	1	055755	12
	PLATE, locking, adjusting ring	1	055761	11
	SPACER, pressure ring guiding CAPSCREW, 5/16"NC x 3/4" LOCKWASHER, 5/16"	ហ្ហាហ	042128 045312 904205	1009
	PIN, actuating lever (3/8" diam., 1-1/8" long)	6	052354	00
	SPACER, adjusting ring retaining screw	2	055757	7
	LEVER, actuating	6	055758	6
		1	055754	UΊ
		15	044753	4
	SPRING, pressure	15	078278	(o
	PLATE, pressure	1	042124	2
7	PLATE ASSEMBLY driven (Has ceramic friction discs)(Used for heavy-duty service only)	1	082909	,-
red	PLATE ASSEMBLY. driven (Has woven facings which are cemented and not serviced separately)(Original equipment)	1	042122	
KIT NUMBER	DESCRIPTION	QTY.	NUMBER	ITEM
	factory option.		Favor	