



Bem. Rem.	Bild Pict.	Nr.	MF-No.	Stck. Qty.	Benennung	Description
	1	395 905 701	2903 134 M91	2	Lenkeinrichtung	Steering device
	2	395 905 701/A	2903 134 T91	2	Lenkeinrichtung	Steering device
	3	395 905 165	2902 983 M1	2	Zwischenring	Intermediate ring
	4	395 905 167	2902 985 M1	4	Haltering	Support ring
	5	395 905 168	2902 986 M1	4	Federblech	Spring plate
	6	990 105 005	1444 132 X1	8	Schraube	Bolt
	7	395 905 170	2902 988 M1	14	Außenlamelle	Outer disk
	8	395 905 169	2902 987 M1	18	Innenlamelle	Inner disk
	9	395 905 742	2903 150 M91	2	Lamellenträger	Disk carrier
	10	395 905 775	2903 177 M91	2	Lamellenträger	Disk carrier
U	11	395 905 744	2903 151 M91	2	Lamellenträger	Disk carrier
1)N	11	395 905 781	2903 183 M91	2	Lamellenträger	Disk carrier
B	12	997 000 355	1444 821 X91	6	O-Ring	O-ring
U	13	994 013 270	3003 316 X1	4	Rillennlager	Groove ball bearing
1)N	13	994 013 178	1444 535 X1	4	Rillenkugellager	Groove ball bearing
U	14	992 770 016	1443 566 X1	4	Sprengring	Circlip
	15	395 905 386	2903 131 M1	1	Ausgleichscheibe 0,3	Shim
	16	395 905 174	2902 992 M1	2	Ölzuführungsflansch	Oil feed flange
	17	990 105 005	1444 132 X1	12	Schraube	Bolt
	18	395 905 172	2902 990 M1	2	Hülse	Sleeve
U	19	997 170 063	3004 962 X1	8	Rechteckring	Rectangular ring
N	19	-	3076 385 M1	8	Rechteckring	Rectangular ring
	20	991 330 019	1444 349 X1	8	Nutmutter	Groove nut
	21	991 741 011	1441 036 X1	4	Sicherungsblech	Retaining plate
B	22	996 731 013	1440 997 X1	12	Dichtring	Seal ring
	23	996 301 005	390 848 X91	6	G-Verschraubung	G-joint
B	24	996 316 003	1443 840 X1	6	Schneidring	Olive
	25	996 315 003	339 995 X1	6	Überwurfmutter	Box nut
	26	395 905 746	2903 153 M91	6	Ölleitung	Oil feed pipe
	27	996 641 005	2999 668 M1	6	Hohlschraube	Hollow bolt
	28	997 170 047	3004 958 X1	8	Rechteckring	Rectangular ring
	29	395 905 161	2902 979 M1	4	Ringkolben	Ring piston
	30	395 905 741	2903 149 M91	2	Welle	Shaft
	31	992 011 067	1444 407 X1	6	Zylinderstift	Cylindrical pin
	32	992 120 093	1444 430 X1	2	Zyl.-Kerbstift	Cyl.-grooved pin
	33	992 120 099	1444 432 X1	2	Zyl.-Kerbstift	Cyl.-grooved pin
	34	992 513 038	1444 456 X1	2	Paßfeder	Key, woodruff
	35	395 905 164	2902 982 M1	2	Anschlagring	Stop ring
	36	997 170 068	3004 964 X1	4	Rechteckring	Rectangular ring
	37	395 905 162	2902 980 M1	36	Druckfeder	Spring
	38	395 905 163	2902 981 M1	18	Schutzrohr	Pipe
	39	395 905 166	2902 984 M1	4	Spannschraube	Clamping bolt
	40	992 011 178	1444 412 X1	4	Zylinderstift	Cylindrical pin
	41	990 105 004	1444 131 X1	8	Schraube	Bolt
	42	395 905 745	2903 152 M91	2	Lamellenträger	Disk carrier
	43	992 011 067	1444 407 X1	8	Zylinderstift	Cylindrical pin
U	44	395 905 171	2902 989 M1	2	Flansch	Flange
N	44	395 905 384	2903 129 M1	2	Flansch	Flange
	45	395 905 385	2903 130 M1	2	Flansch	Flange
	46	990 105 027	3004 453 X1	6	Schraube	Bolt

1) zusammen einbauen  
to be installed together  
à monter ensemble  
a instalarse juntos  
da montare insieme

2) für Rillennlager )  
for deep groove ball bearing )  
pour roulement rainuré ) 994 013 270 - und Sprengring )  
pararodamiento de bolas ranurado )MF 3003 316 X1 - et segment d'arrêt ) 992 770 016 -  
per cuscinetto a siera ) y anillo retèn ) MF 1443 566 X1  
e anello elastico )

bei alten Lamellenträger einbauen )  
installed by old disk carrier )  
installer au lieu des vieux supports disque ) 395 905 744 - MF 2903 151 M91  
instalar en lugar de porta discos antiguo )  
installare in caso di portadischi tipo vecchio )