

ITEM	PART NO.	QTY.	DESCRIPTION
1	656790	1	PINION, bevel (12 teeth)
2	629355	1	RING, snap, bearing retaining
3	905360	1	BALL, retaining, rear bearing (3/8" diam.)
4	644337	1	BEARING, roller, rear end
5	657313	1	SPACER, first speed gear
6	925241	1	O-RING, rear bearing retainer
7	653740 917733	1 6	RETAINER, rear bearing CAPSCREW, socket-hd., 3/8"NC x 1-1/4"
8	925652	1	O-RING, rear bearing retainer
9	648619	1	SEAL, oil
10	656594	1	GEAR, first speed (59 teeth)
11	656593	1	GEAR, third speed (39 teeth)
12	629356	1	SLEEVE, gear spacing
			(Continued)

TRANSMISSION BEVEL PINION SHAFT (Continued)

ITEM	PĄRT NO.	QTY.	DESCRIPTION
13	656597	1	GEAR, second speed (48 teeth)
14	656598	1	GEAR, idling (53 teeth)
15	629138	1	RING, snap, idling gear
16	657324	1	BEARING, roller (Consists of 2 roller assemblies, 2 cups and 1 spacer. Serviced only as a unit)
17	657318	1	BEARING, roller, front end (Consists of 2 roller assemblies, 1 cup and 1 spacer. Serviced only as a unit)
	657315	7	SHIM, pinion adjustment (.005" thick)
18	657315 657316 657317	5	SHIM, pinion adjustment (.007" thick) Use as required
	657317	7	SHIM, pinion adjustment (.010" thick)
19	657302	1	RING, snap, front bearing
20 21 22	662411 035018 629358	1 3 1	RETAINER, front bearing, inner CAPSCREW, 1/2"NF x 1-1/2" PLATE, capscrew locking
23 {	657312	5	SHIM, bearing retainer (.005" thick) Use as required
	657312	5	SHIM, bearing retainer (.005" thick) SHIM, bearing retainer (.007" thick) Use as required
24 25 26 27	653819 028979 916317 916321 904208 910244	1 3 2 3 8 2	RETAINER, front bearing, outer CAPSCREW, 1/2"NC x 2-1/2" CAPSCREW, 1/2"NC x 2-3/4" CAPSCREW, 1/2"NC x 4-1/2" LOCKWASHER, 1/2" WASHER, plain, SAE std., 1/2"
28		-	PUMP (See SHIFT INHIBITING PUMP AND LINES)