


	PART	_			PACKAGE
ITEM	NUMBER	QTY.	DESCRIPTION		NUMBER
1	050275	2	CUP, inner bearing		
2	064200	2	CONE ASSEMBLY, inner bearing		
3	068501	2	GEAR (44 teeth)		
4 5 6	049829 035244 049936	4 4 4	LOCK, gear retaining CAPSCREW, 3/8"NC x 3/4" LOCK, capscrew		
7	051246	2	SHAFT		
8	049886	2	PINION (20 teeth)		
9	051438	2	CONE ASSEMBLY, outer bearing		
10	051347	2	CUP, outer bearing		
	051450	4	SHIM, bearing adjustment (.005" thick.	Use as req!d)	
. 11	051448	4	SHIM, bearing adjustment (.007" thick.	Use as req'd)	
	051449	10	SHIM, bearing adjustment (.010" thick.	Use as req'd)	
12 13	051243 013058 904206	2 12 12	COVER, outer bearing CAPSCREW, 3/8"NC x 1-1/4" LOCKWASHER, 3/8"		




FINAL DRIVE SPROCKET SHAFT AND GEAR

* Used prior to tractor serial No. 8906 ** Effective with tractor serial No. 8906 PART QTY. PACKAGE ITEM NUMBER >< ** DESCRIPTION NUMBER GEAR (51 teeth) LOCK, gear retaining CAPSCREW, 3/8"NF x 1" LOCK, capscrew SEAL, shaft end cover (1/4" thick) (Used prior to 2. tractor #3491) RING, sealing, shaft end cover (1/8" thick) (Effective 2. with tractor #3491) COVER, shaft end, inner (Used prior to tractor #3491) 2. COVER, shaft end, inner (Effective with tractor #3491) CUP, inner bearing CONE ASSEMBLY, inner bearing SHAFT, track sprocket (6 splines) (Original equipment) SHAFT, track sprocket (20 splines) (Service replace-ment only) CONE ASSEMBLY, intermediate bearing (3-1/4"I.D.) (Original equipment) CONE ASSEMBLY, intermediate bearing (3-3/8"I.D.) (Service replacement only. Used with 20-spline shaft only) CUP, intermediate bearing SHIM, bearing adjustment (.005" thick. Use as req'd) SHIM, bearing adjustment (.007" thick. Use as req'd) SHIM, bearing adjustment (.010" thick. Use as req'd) RETAINER, intermediate bearing GUARD, inner seal CAPSCREW, 1/2"NC x 1-1/2" LOCKWASHER, 1/2" BOOT, inner seal FOLLOWER ASSEMBLY, inner seal (Serviced only RING, inner seal (stationary. 5''I.D.) RING, inner seal (stationary, 5-3/16"I.D.) (Continued)

(Revised February 1961)

FINAL DRIVE SPROCKET SHAFT AND GEAR (Continued)

	PART	QTY.	PACKAGE
ITEM	NUMBER	* **	DESCRIPTION NUMBER
19	082859 096159	2 -	RING, inner seal (rotating, 6-13/16"O.D.) 073762
19 {			RING, inner seal (rotating, 7-1/2''O.D.) 096278
20	053594 096160	2 -	RING, packing, seal ring (rubber, 5-5/16"O.D.) 073762
20 7	096160	- 2	RING, packing, seal ring (rubber, 5-7/8"O.D.) 096278
	049853	2 -	LOCK, sprocket retaining nut (6-3/8"O.D., 3-3/4"hex) (Original equipment)
21	096155	- 2	LOCK, sprocket retaining nut (7-3/4"O.D., 3-3/4" hex) (Original equipment)
	621243	2 2	LOCK, sprocket retaining nut (4" hex) (Service replacement. Used with 20-spline sprocket only)
22	035439	$\begin{array}{ccc} 4 & 4 \\ 4 & 4 \end{array}$	CAPSCREW, 3/8"NC x 1" LOCKWASHER, 3/8"
	904206		·
23 4	081369	2 2	NUT, sprocket retaining (Original equipment) NUT, sprocket retaining (Service replacement. Used
23 {	621241	2 2	NUT, sprocket retaining (Service replacement. Used with 20-spline sprocket only)
	049817	2 -	SPROCKET ASSEMBLY, track (Includes item 25) (Standard. Has 5" diam. hub with 6 splines and wide toothbase) (Original equipment)
	096146	- 2	SPROCKET ASSEMBLY, track (Includes item 25) (Stand- ard. Has 5-3/16" diam. hub with 6 splines and wide tooth-base) (Original equipment)
!	621237	2 2	SPROCKET ASSEMBLY, track (Includes item 25) (Service replacement. Has 20 splines and wide tooth base)
24	056188	2 -	SPROCKET ASSEMBLY, track (Includes item 25) (Special. Has 5" diam. hub with 6 splines and narrow tooth-base to minimize packing of track)
	096167	- 2	SPROCKET ASSEMBLY, track (Includes item 25) (Special. Has 5-3/16" diam. hub with 6 splines and narrow toothbase to minimize packing of track)
3	621225	2 2	SPROCKET ASSEMBLY, track (Includes item 25) (Service replacement. Has 20 splines and narrow tooth-base to minimize packing of track)
	097960	2 2	SPROCKET RIM, only (Standard type. Requires welding to install)
25	042930	6 6	PIN, driving, inner seal ring
26	033288		CEMENT, neoprene, 1/2 pt. can For cementing
27	054890		SOLVENT, neoprene, cement, 1/2 pt. can seal boots




on the grand out

FINAL DRIVE PINION SHAFT

* 44" tread Models ** 60" tread Models

ITEM	PART NUMBER		Γ Υ. **	DESCRIPTION	PACKAGE NUMBER
1	050216	2	2	DRUM, brake	
2 3	049937 035221 904208	- - -	2 16 16	HUB, brake drum CAPSCREW, 1/2"NC x 1" LOCKWASHER, 1/2"	
4	050264	-	2	SEAL, oil (neoprene)	
5	050226	-	2	CAPSCREW, hub retaining (1"NF x 1-3/4")	
6	050225	_	2	WASHER, locking, hub retaining capscrew	
7	064520	-	2	WASHER ASSEMBLY, hub retaining (Includes item 8)	
8	035793	-	2	PIN, hub retaining washer	
9	053670	2	2	SEAL, oil	
10 11	049820 922211 90420 6	2 12 12	2 12 12	CAGE, inner bearing CAPSCREW, Nylok, 3/8"NC x 1-1/4" LOCKWASHER, 3/8"	
12	051245	2	2	GASKET, inner bearing cage	. 069625
13	050274	2	2	BEARING, roller, inner	
14	049945	-	2	SHAFT	
15	040831	-	2	RING, snap, intermediate bearing	
16	063912	-	2	BEARING, roller, intermediate	
17	049899	2	2	RING, snap, pinion shaft	
18	049881	2	2	PINION (20 teeth)	
19	050273	2	2	BEARING, roller, outer	
20	049903	2	2	GASKET, outer bearing cover	. 069625
21 22	049818 013058 904206	2 8 8	2 8 8	COVER, outer bearing CAPSCREW, 3/8"NC x 1-1/4" LOCKWASHER, 3/8"	
23 24	049822 207781 904208		-	HUB, brake drum CAPSCREW, 1/2"NC x 1" (thin head) LOCKWASHER, 1/2"	



* Original equipment

** Service replacement. Used with 20-spline track

spreaket only

		0.1		sprocket only	DAGRAGE
ITEM	PART NUMBER		ΓΥ. **	DESCRIPTION	PACKAGE NUMBER
1 {	049109	2	-	BOOT, seal	073763
	051112	-	2	BOOT, seal	088665
2 {	049111	2	-	SPRING ASSEMBLY, seal (Serviced only as a unit)	073763
	051121	-	2 .	SPRING ASSEMBLY, seal (Serviced only as a unit)	
3 {	049110	4	-	RING, seal	073763
	051124	-	4	RING, seal	088665
₄ ∫	049836	2	_	GASKET, seal ring	073763
4 {	051125	-	2	GASKET, seal ring	088665
5	081194	12	12	STUD, locating, seal ring (Rivets to cage)	
6	085726	12	12	SHIM, outboard bearing cage (.015" thick. Use as req'd)	
7	085834	2	-	CAGE ASSEMBLY, outboard bearing (Includes item 5)	
(]	621245	-	2	CAGE ASSEMBLY, outboard bearing (Includes item 5)	
8	080101 > 6293	2 54	2	BEARING, roller (Each consists of 1 roller assembly and cups. Serviced only as a unit)	
9	081242 915513	2 2	2 2	NUT, retaining, outboard bearing PIN, roll, 1/4" x 3/4"	

(Continued)

FINAL DRIVE OUTBOARD BEARING AND SEAL (Continued)

70000	PART		Y. **	DECCRIPTION	PACKAGE NUMBER
ITEM	NUMBER	7,5	**	DESCRIPTION	NOMBER
1	085827	4	4	SHIM, bearing adjustment (.005" thick. Use as req'd) SHIM, bearing adjustment (.007" thick. Use as req'd) SHIM, bearing adjustment (.010" thick. Use as req'd)	
10{10}	0.8582.9	4	4	SHIM, bearing adjustment (.007" thick. Use as req'd)	
	085828	10	10	SHIM, bearing adjustment (.010" thick. Use as req'd)	
`	003020				
11	085831	2	2	CAP, outboard bearing	
12	035068	12	12	CAPSCREW, $1/2$ "NF x 2-1/4"	
13	035525	4	4	CAPSCREW, $1/2$ "NF x $1-1/8$ "	
	904208	16	16	LOCKWASHER, 1/2"	
14	085832	2	2	GUARD, track sprocket (Special equipment)	
15	070469	4	4	CAPSCREW, $1/2$ "NF x $1-1/4$ "	
	900818	4	4	WASHER, plain, U.S. std., 1/2"	
16	614478	4	4	CAPSCREW, $1/2$ ''NF x 1-3/8''	
	904208	8	8	LOCKWASHER, 1/2"	
17	064531	4	4	WASHER, plain	
				· · · · · · · · · · · · · · · · · · ·	
18	033288	-		CEMENT, neoprene, 1/2 pt. can For cementi	nσ
				hoote and ca	∽s skets
19	054890	_	-	SOLVENT, neoprene cement, 1/2 pt. can	51000
				•	